

**SYSTEM FOR PROVIDING CONTINUITY BETWEEN SESSION CLIENTS
AND METHOD THEREFOR**

Background of the Invention

5

Field of the Invention

This invention relates in general to communication systems and in particular to communication systems incorporating capabilities to provide continuity of real time action information among a plurality of session clients.

10

Description of the Related Art

An auction is the buying and selling of property through open public bidding. Typically, potential purchasers make a succession of increasing bids or offers until the auctioneer accepts the highest (and final) bid. At a Dutch auction, by contrast, the seller offers property at successively lower prices until one of his offers is accepted or until the price drops so low as to force the withdrawal of the offered property. Prospective buyers are usually allowed to examine auction items beforehand, and sellers can set a minimum price below which the property will not be sold. Auctions are important in the agricultural markets of many countries, permitting the rapid sale of perishable goods. Other items often sold at auction include artwork and antiques, secondhand goods, and farms and buildings repossessed by banks or the government. Auction selling is also employed on stock and commodity exchanges.

15

20

Historically, potential buyers meet at a geographical location to participate in an auction. This method tends to limit the number of potential buyers to the available population that are physically near the geographical location of the auction. Potential buyers make the conscious decision to attend an auction after receiving advertisement

5 by word of mouth or via various media channels such as the newspaper. Potential buyers show up prior to the auction start time and inspect potential items to bid on. As the auction starts, one item at a time is auctioned off through a person called the auctioneer. The auction usually lasts for a brief part of the day with the financial transactions between each buyer and seller being resolved before the end of the

10 auction. Usually the auctioneer or auction house will generate revenue by receiving a percentage of the item sold or alternatively can have a flat rate for each item sold. An auction that requires physical presence at a geographical location has limits on the number of items that can be sold within an allotted time period, the number of people present in a geographical auction location, and the effects on the auction price.

15 Recently, the ubiquitous nature of the Internet has fueled the growth of online electronic auctions. Now a larger number of buyers can be reached as they enjoy bidding for an item in the comfort of their home or other surroundings without physically being at the geographical location of the auction. Benefits of the online auction include alleviation of the requirement to be physically at a geographical

20 location, the potential for reaching a larger number of people through the ubiquitous nature of the Internet, capability for many items to be auctioned off at the same time, capability for the auction time to continue for several days. However, at the same time online auctions enjoy these benefits, drawbacks include lack of mutual trust between

seller and buyer, need to visualize the product description and shape, and reduction of participation due to limited access to the Internet at a buyer's current location.

Online auction houses provide their services through online servers including database storage of buyer and seller profiles and auction items. The auction house

- 5 provides services that allow the user to search by a particular interest, receive notification of available items of particular interest, rate or provide a trust level for buyer and seller, provide a seller with a virtual store front, maintain an overview page of items created by a buyer, receive notification in price changes for buyer and seller, create escrow account to exchange money and merchandise. Online auction houses
- 10 generate revenue for operation by charging a fee based upon the percentage of the sales price, providing other services such as escrow accounts, and through selling online advertisements.

Online auction houses allow the buyer to browse items for sale by utilizing a search engine that locates particular items of interest. A buyer will usually set up a

- 15 profile that is accessible by username and password and contains such items as auction interests. Notifications by electronic mail can be sent to the perspective buyer once a seller has listed an item that matches the buyer's interest. The auction house provides as part of the buyer's profile a personal storable listing that includes items they are currently bidding on, items they are following, and items they have won. The
- 20 buyer can add to the list from auction items they are interested in or want to bid on.

The online auction house gives the capability to the seller to create a virtual storefront or to list items independently. The seller, like the buyer, creates a user account by supplying a username and password and contact information. The seller has the ability to create a unique motif for their virtual storefront. The seller will

normally provide a description along with a picture of the item to sell and possibly a hyperlink to the manufacturer of the item that can be used to provide relative cost comparison. In addition, the seller can leave contact information so that the perspective buyer can have a dialogue with the seller. The seller, in some cases, can
5 desire to have a minimum reserved price for an item or service. The minimum sale price is usually not made public while bidding on an item, but will be indicated in the listing information when the minimum reserved price has been reached. The seller has the ability to list all of his items within one listing of his virtual storefront.

The online auction house helps foster a sense of mutual trust by providing
10 rating methods for both buyers and sellers. Buyer and seller ratings include such items as the number of transactions performed, the measure of performance or satisfaction, and the history information. Either a perspective buyer or a seller can enter these ratings. Based upon past performance or execution, a buyer or seller can begin to realize a feeling of trust without ever meeting the person they are selling to or buying
15 from. In addition, the online auction house will provide escrow services to the buyer and/or seller. The auction house will typically hold the form of payment, until the buyer receives the item or service. Buyers and sellers with limited history or poor performance typically use the escrow service. One of the many benefits of having a superior seller's rating is that the seller can create brand or seller loyalty based on past
20 auction. As with other financial business transactions there are some bidders that have either fraudulent behaviors or dislikes toward a certain seller. A seller can utilize the blacklist service to deny a potential fraudulent or unhappy buyer from participating in any of the seller's online auctions.

A seller who places an item up for auction will also include the duration of the auction. Typically the activity on an auction will start out slow with the activity reaching the apex at the very end of the auction. A desiring bidder will soon realize that they must have online bidding presence toward the end of the auction. The bidder for an item up for auction has the option to either manually participate in the bidding process or to utilize the online auction house's automated bidding mechanism. The manual process is usually the preferred method where the bidder will follow the online bidding history and update their bid as needed to retain the highest bid price up to the bidder's highest willing bid price. As the close of the auction nears, the bidder will actively compete with other buyers to retain the highest bid price. As a compliment to the manual bid process, the online auction house typically provides an automated bidding agent that acts on the behalf of the buyer whether are not they are physically connected to the online auction. The buyer will select the item to bid and enter their starting bid price along with a maximum bid price that they are willing to pay for that item or service. The buyer's maximum bid price is not visible to other users within the online auction house. The agent, unlike the buyer, always knows the minimum reserved price, if any, set by the seller and will increment the bid price to the minimum reserved price if this price is within the buyer's maximum bid price. As part of the buyer's bidding process, notification of events relating to the auction item(s) are sent to the buyer typically through electronic mail. The types of events in which the buyer will be notified by the online auction house include no longer being the highest bidder, the end of auction results (winning bid), and the remaining time on auction.

Without the aid of an online agent, a buyer will receive the auction item or service if he/she is the highest bidder and has an active presence toward the end of the auction. Unfortunately, the expiration time of the auction does not always coincide with the buyer's schedule of daily activities. The buyer can have to leave an online
5 auction to perform other daily duties and as result can miss the competitive bidding at the end of the auction.

Gambling is the act of a person wagering against an opposing person(s) as to the outcome of an event. Many people enjoy the traditional forms of gambling such as boxing, horse and dog racing, and sporting events such as football, basketball, soccer,
10 baseball and hockey. These types of gambling events are not usually paused or suspended to be completed at a later time and are referred to as real time gambling events. Types of gambling events that can be suspended or delayed to a later time are card games and slot machines.

Traditionally, a bet or a wager is placed with a bookkeeper on the outcome of
15 an event. The bookkeeper will generate revenue by charging a percentage of proceeds earned by a gambling participant. In addition, the bookkeeper will track the wagers placed by the participants and the progress of the gambling event itself. Usually the bookkeeper will vary the odds of the event as to balance or bring equality to the gambling event. For example, a soccer team can be given two goals to their final
20 score, since the opposing soccer team is viewed to be better then them by two goals.

During a gambling event, odds for the outcome can change to reflect a new equality between participants, therefore, gambling participants will benefit by being able to receive and act upon the new odds in real time. In addition, late breaking news prior and during a gambling event can change the outcome of the gambling event,

thereby creating a need for the gambling participant to be able to receive and act upon this information. Likewise, the history surrounding a gambling event can be beneficial to a participant that is able to receive and act upon this information in real time.

- 5 Technological advances in the Internet now provide the capability for online gambling to utilize an Internet server to perform the roll of bookkeeper. Some of the advantages of online gambling are providing for online gamblers to view the latest changes in odds, easier tracking of monies won/loss, social / language barriers are easier to overcome while providing a safe surrounding environment, gambling
- 10 participants can learn through free practice sessions at their own speed, electronic commerce eases collection problems. Some potential disadvantages in the technology advancements of online gambling are the potential for anonymous money laundering, the complexity of distribution of winnings, the increased risk of children gaining access to gambling sites, and the increased risk of a gambler becoming
- 15 engrossed in the gambling event.

- Online sessions such as online auctions and online gambling include data that is time and action sensitive, having little or no value after the auction or gambling time has expired. Further, online sessions can continue for several days. Although the online session participant benefits from staying informed and involved, it is
- 20 difficult to remain available to the fixed session client monitoring the online session.

Recently, to meet the needs of session participants who cannot remain at a fixed location and/or device having a session client, online services are providing wireless access to their services and associated Internet site using Internet enabled wireless devices such as cellular telephones and pagers. The Internet enabled cellular

telephone, for example, can include a session client with the same functionality as a session client within a fixed device such as a personal computer. Similarly, a pager can receive alerts relating to the status of a particular online session. One drawback of real time actionable events experienced in online auctions and gambling is that the

5 times of the events do not always coincide with the user's preferred method of online participation.

With today's technology, when participating in an online session, in order to switch to a different session client, the account user disconnects the currently connected session client from the online server. The account user then later, at the

10 appropriate event time, connects a second session client to the online server and logs in. Finally, the account user reinitiates each online session that was in progress on the first session client. The disadvantage of this method is the numerous manual operations required of the account user to change session clients including remembering the appropriate event time to start the new session client.

15 Therefore, what is needed is a system and method for the transferring of real time event information associated with one or more online sessions between different session clients allowing the seamless continuation of participation in the online sessions.

Brief Description of the Drawings

20

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote similar elements, and in which:

FIG. 1 is an electronic block diagram of an online communication system, in accordance with the preferred embodiment of the present invention;

FIG. 2 illustrates an online server for use within the online communication system of FIG. 1, in accordance with the preferred embodiment of the present invention;

FIG. 3 illustrates an online account user for use within the online server of FIG. 2, in accordance with the preferred embodiment of the present invention;

FIG. 4 illustrates an online session for use within the online server of FIG. 2, in accordance with the preferred embodiment of the present invention;

FIGs. 5 and 6 illustrate various embodiments of session data for use within the online session of FIG. 4, in accordance with the preferred embodiment of the present invention;

FIG. 7 illustrates a session history for use within the online session of FIG. 4, in accordance with the preferred embodiment of the present invention;

FIG. 8 illustrates a session client for use within the online communication system of FIG. 1, in accordance with the preferred embodiment of the present invention;

FIG. 9 illustrates client data for use within the session client of FIG. 8, in accordance with the preferred embodiment of the present invention;

5 FIGs. 10, 11, and 12 are electronic block diagrams of various embodiments of a session device in which a session client of FIG. 8 operates;

FIGs. 13 to 16 are electronic block diagrams of various embodiments of the online communication system of FIG. 1, in accordance with the preferred embodiment
10 of the present invention; and

FIGs. 17 to 21 are flowcharts illustrating the operation of the online communication system of FIG. 1, in accordance with the preferred embodiment of the present invention.

15

Detailed Description Of The Preferred Embodiment(s)

As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary
20 of the invention, which can be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present invention in virtually any

appropriately detailed structure. Further, the terms and phrases used herein are not intended to be limiting; but rather, to provide an understandable description of the invention.

Referring to FIG. 1, an electronic block diagram of an online communication system **10** in accordance with the present invention is shown. As illustrated, the online communication system **10** preferably includes a plurality of session clients **12** for communication with a plurality of online servers **14**, preferably interconnected through the well-known worldwide Internet computer network **16**. Each of the plurality of session clients **12** such as a first session client **18** and a second session client **20** includes client software to interface within the online communication system **10**. Each of the plurality of session clients **12** can be a client residing on a user's session device such as a personal computer, a Cable set top box, an xDSL home gateway, a satellite gateway, a wireless gateway, or an equivalent. It will be appreciated by one of ordinary skill in the art that in accordance with the present invention, the interface capabilities of the client software can also be designed into client hardware of a session client. Each session client **22** of the plurality of session clients **12** further includes a client identifier **24**. For example, the first session client **18** includes a first client identifier **26** and the second session client **20** includes a second client identifier **28**. The client identifier **24** of the session client **22** is a unique identification within the online communication system **10** for directing information and data to a particular session client within a session device. For example, the client identifier **24** can be an address of a mobile device or an IP address and number of the port of a fixed network device. To communicate with at least one of the plurality of

online servers **14**, the session client **22** establishes a communication connection **30**. For example, the first session client **18** establishes a first communication connection **32** via the Internet computer network **16** for communication with at least one online server **34** of the plurality of online servers **14** such as the first online server **36** and/or

5 the second online server **38**. Similarly, the second session client **20** establishes a second communication connection **40** for communication with at least one of the plurality of online servers **14**. It will be appreciated by one of ordinary skill in the art that the communication connection **30**, the first communication connection **32**, and the second communication connection **40** can be a physical connection, or

10 alternatively can be a logical connection where the act of connecting and disconnecting is a logical one. Further, each communication connection can be a broadband connection such as Digital Subscriber Line (DSL) or cable television, or could utilize a narrowband connection like an analog modem. Each session client **22** of the plurality of session clients **12** is operated by at least one account user **42**. The

15 account user **42** is an individual who uses one or more session clients to communicate with the plurality of online servers **14** along with other account users. It will be appreciated by one of ordinary skill in the art that the account user **42** can communicate using one or more session clients. For example, a first account user **44** can establish communication with the plurality of online servers **14** using the first

20 session client **18**, and, in accordance with the present invention, also using the second session client **20**.

Each session client **22** preferably includes a plurality of client data **46**. The plurality of client data **46** includes data associated with the session client **22** and data

associated with each online session for which the session client **22** is currently participating, has participated in, or plans to participate in within one or more of the plurality of online servers **14**. The plurality of client data **46** can be divided up into one or more client data portions **48** as illustrated in FIG. **9**. The first session client **18**
5 includes a first client data **50** and the second session client **20** includes a second client data **52**.

FIG. **2** illustrates the online server **34** for use within the online communication system **10** of FIG. **1**, in accordance with the preferred embodiment of the present invention. It will be appreciated by one of ordinary skill in the art that the online
10 server **34** as illustrated in FIG. **2** can be any of the plurality of online servers **14** of FIG. **1** such as the first online server **36** and the second online server **38**. The online server **34** manages a plurality of online sessions **54** among the plurality of session clients **12**, facilitating substantially real time session participation among the plurality of session clients **12** within the online communication system **10** of FIG. **1**. The
15 plurality of online sessions **54**, for example, can be an online auction session, an online gambling session, or any equivalent action sensitive online session. The online server **34** provides numerous services to manage the plurality of online sessions **54**. The online server **34** also offers various options to the plurality of online account users **56** to reduce cost or enhance the features of the plurality of online sessions **54**.
20 The online server **34** includes a server data **58**. The server data **58** preferably includes a server identifier **60** for the online server **34**. The server identifier **60** can be, for example, a unique selective call address in a wireless communication system. Alternatively, the server identifier **60** can be an IP address, or an IP address and

associated number of the port assigned to the online server **34** of a wired communication system. It will be appreciated by one of ordinary skill in the art that the server identifier **60** can be one mentioned herein or an equivalent. The server identifier **60** enables the communication between the plurality of session clients **12** and the online server **34** using the communication connections such as the communication connection **30**, the first communication connection **32**, and the second communication connection **40** of FIG. 1. The server data **58** also preferably includes a server profile **62**. The server profile **62** includes information regarding the capabilities of the online server **34**. For example, the server profile **62** can include server processing power, server client capability, server session capability, and server access to secondary networks. It will be appreciated by one of ordinary skill in the art that the server profile **62** can include any of those mentioned above in any combination or an equivalent.

FIG. 3 illustrates data stored in the online server **34** of FIG. 2 for an online account user **64**, in accordance with the preferred embodiment of the present invention. The online account user **64**, for example, can be a first online account user **66** and/or a second online account user **68** as illustrated in FIG. 2. Further, the online account user **64** can be the account user **42** and/or the first account user **44** of FIG. 1. For example, as illustrated, the online server **34** stores an account identifier **70**, an account password **72**, an account contact information **74**, an account preferences **76**, and an account commerce **78**. The account identifier **70** is preferably a user name or other identification of the online account user **64**. The account password **72** is preferably a codeword or the authentication key **166** created and/or known only by the

online account user **64** to provide security for access of account information and online session participation. For example, once the online account user **64** is logged into the online server **34**, the online account user **64** would be required to input the account password **72** for each financial transaction and setting change. The account contact information **74**, for example, can include account user presence, account user availability, account phone number, account mailing address, or account user preferred communication means. It will be appreciated by one of ordinary skill in the art that the account contact information **74** can be any of the contact information mentioned herein or an equivalent.

The account preferences **76** can for example include favorite topics, associates, group lists, age, obscenity rating, and optional services. The account preferences **76** further can include text font attributes, filter settings, blocking settings, screen names per account identifier, alert settings per screen name, buddy list groups, electronic mailboxes, electronic voice mail, and parental control settings. It will be appreciated by one of ordinary skill in the art that the account preferences **76**, in accordance with the present invention, can include any of those preferences mentioned herein or an equivalent.

The account commerce **78** can include billing information such as credit card information or an equivalent for electronically billing the online account user **64**. It will be appreciated by one of ordinary skill in the art that each online account user **64** can have one or more accounts. For example, the online account user **64** can have a business account and a personal account both operated using one or more of the plurality of session clients **12**.

FIG. 4 illustrates a plurality of session information **182** for an online session **80** for use within the online server **34** of FIG. 2, in accordance with the preferred embodiment of the present invention. The online session **80** can be any of the plurality of online sessions **54** such as a first online session **82** and/or a second online session **84** as illustrated in FIG. 2. As illustrated in FIG. 4, for each online session **80**, the online server **34** preferably stores a session identifier **86**, a session priority **88**, a plurality of session preferences **90**, a plurality of session participants **92**, a plurality of session data **94**, a session history **96**, and one or more Internet cookie(s) **97** per session. It will be appreciated by one of ordinary skill in the art that the plurality of session information **182** stored in the online server **34** for the online session **80**, in accordance with the present invention, can include any of the session information mentioned herein or an equivalent.

Preferably, the session identifier **86** identifies the online session **80** of the plurality of online sessions **54**. In one embodiment, the online session **80** is assigned the session priority **88**. The session priority **88** determines or identifies the priority of the online session **80** within the plurality of online sessions **54** currently active within the online server **34**. The session priority **88** can be set through a predetermined algorithm in the online server **34** taking into account the various characteristics of the online session **80**. The session priority **88** can for example, specify a communication priority order, an information updating priority order, and/or a session processing order. It will be appreciated by one of ordinary skill in the art that the session priority **88** can specify any of the priorities mentioned herein or an equivalent.

The plurality of session preferences **90** defines certain attributes settable by the online session owner. The plurality of session preferences **90**, for example, can include text font attributes, filter settings, blocking settings, alert settings, screen names, buddy list groups, electronic mailboxes, parental control settings, an alert option such as alert on receipt of a new real time session event or no alert on receipt of a new real time session event, guaranteed or non-guaranteed delivery, timeout setting for participation in the online session **80**, and number of session events and/or messages to retain in the session history **96**. It will be appreciated by one of ordinary skill in the art that the plurality of session preferences **90**, in accordance with the present invention, can include any of the session preferences mentioned herein or an equivalent. In one embodiment, the plurality of session preferences **43** includes a session timer. The session timer is a preset time period upon which the online session **80** is active.

In one embodiment, the plurality of session preferences **90** includes one or more Internet cookie(s) per session. The session Internet cookie is a piece of information that is maintained on the session client **22** by the online server **34**. Information contained with the session Internet cookie can, for example, contain the session device type and capabilities, the software application version, and advertisement interests. The session Internet cookie is processed based on a two-stage process. First the session Internet cookie is stored in the online account user's device such as the session device containing the session client **22**, normally without the online account user's knowledge. One of the functions of the session Internet cookie is to provide personal customization when an online website is re-visited. For example, with

customizable web search engines the online account user **64** selects categories of interest from the online website page. The online server **34** then creates a specific session Internet cookie, which is essentially a tagged string of text containing the user's preferences, and it transmits this session Internet cookie to the online account

5 user's device. The online account user's web browser, if cookie-savvy, receives the session Internet cookie and stores it in a special file called a cookie list.

During the second stage, the session Internet cookie is automatically transferred from the online account user's device to the online server **34**. Whenever the online account user **64** directs their web browser to display a certain web page

10 from the online server **34**, the browser will transmit the session Internet cookie containing personal information to the online server **34** whereby the online server **34** formats the content in a personalized manner including directed advertisements.

The plurality of session participants **92** includes each of the plurality of online account users **56** participating in the online session **80** along with the online account

15 user data as illustrated in FIG. 3.

The plurality of session data **94** includes all pertinent data and information related to the online session **80**. FIGs. **5** and **6** illustrate two examples of the plurality of session data **94** in accordance with the preferred embodiment of the present invention. It will be appreciated by one of ordinary skill in the art that the plurality of

20 session data **94** can include the session data illustrated in FIGs. **5** and **6** or an equivalent.

FIG. **5** illustrates an auction session data **98** stored by the online server **34** when the online session **80** is an online auction session. Preferably, the auction session data

98 includes an item name **100**, an item number **102**, an item description **104**, a navigational path **106**, an auction house **108**, an end time **110**, a number of bidders **112**, a reserve price **114**, and a current status **116**. It will be appreciated by one of ordinary skill in the art that the auction session data **98** as illustrated in FIG. 5, in accordance with the present invention, can include those items mentioned herein or an equivalent. For example, the auction session data can include an auction type.

The navigational path **106** can include, for example, a navigational path to the item of interest, for example a Uniform Resource Locator (URL) of the item within the online auction session. URLs are short strings that identify resources in the Internet computer network **16** including documents, images, downloadable files, services, electronic mailboxes, and other resources. They make resources available under a variety of naming schemes and access methods (such as HTTP (Hypertext Transfer Protocol), FTP (File Transfer Protocol), and Internet protocol) mail addressable in the same simple way.

FIG. 6 illustrates a gambling session data **118** stored by the online server **34** when the online session **80** is an online gambling session. The gambling session, for example, can be a real time gambling session such as horse and/or dog racing, boxing matches, football, basketball, soccer, baseball, hockey games and car and/or boat racing. Further, the online gambling session can be non-real time such as server-based card games where a player can suspend play and return later, and/or a slot machine session. Preferably, the gambling session data **118** includes an event name **120**, an event number **122**, an event description **124**, a navigational path **126**, a gambling house **128**, a start time **130**, an end time **132**, a number of gamblers **134**, a

current status **136**, and an event monitoring **138**. The navigational path **126** can include, for example, a URL of the event of interest in the online gambling session. It will be appreciated by one of ordinary skill in the art that the gambling session data **18**, in accordance with the present invention, can be any of the data mentioned herein or an equivalent.

FIG. 7 illustrates the session history **96** for use within the online session **80** of FIG. 4, in accordance with the preferred embodiment of the present invention. As illustrated in FIG. 7, the session history **96** preferably includes a plurality of session entries **140** in which each session entry **142** is associated with a plurality of entry information including the account identifier **70** for an associated entry originator such as the online account user **64**. The associated entry originator, for example, is one of the plurality of session participants **92**. Each session entry **142** further can be associated with a timestamp **144** identifying the time that the session entry **142** was entered into the online session **80** by the entry originator. The session history **96** is further composed of at least one session portion **146**. Each session portion **146** comprises at least one session entry **142** and associated information. It will be appreciated by one of ordinary skill in the art that although the session portion **146** is illustrated as a portion of the session history **96**, alternatively, in accordance with the present invention, the session portion **146** can be any portion of the plurality of session data **94**.

FIG. 8 illustrates the session client **22** for use within the online communication system **10** of FIG. 1, in accordance with the preferred embodiment of the present invention. It will be appreciated by one of ordinary skill in the art that the session

client **22** as illustrated in FIG. **8** can be any of the plurality of session clients **12** illustrated in FIG. **1** such as the first session client **18** and/or the second session client **20**. The session client **22** preferably includes the plurality of client data **46**, the client identifier **24**, a browser **148**, a plurality of current sessions **150**, a session polling **152**,
 5 a session transfer **154**, and a plurality of transfer clients' profiles **156**.

The browser **148** preferably includes a plurality of launch preferences **158** and a plurality of alert preferences **160**. The browser **148** is preferably a software application programmed within the session client **22** the online account user **64** to find and view information on the plurality of online servers **14** via the Internet computer
 10 network **16**. The browser **148**, for example can be a text-based browser using "point-and-click" graphical manipulations. The browser **148** can preferably interpret the Hyper Text Markup Language (HTML) tags in downloaded documents and format the displayed data according to a set of standard style rules. The browser **148** can be hard coded or programmed into the session device, with which the session client **22**
 15 resides, during manufacturing, can be programmed over-the-air upon customer subscription, or can be a downloadable application. It will be appreciated that other programming methods can be utilized for programming the browser **148**. It will be further appreciated by one of ordinary skill in the art that the browser **148** alternatively can be hardware circuitry. The plurality of launch preferences **158** within the browser
 20 **148** includes data programmable by the online account user **64** such as when the session client **22** will launch and connect to the online server **34**. For example, the online account user **64** can program the plurality of launch preferences **158** to launch the session client **22** at a predetermined time prior to the end time **110** of an online

10072672.020002
 auction session or the end time 132 of an online gambling session to allow the online account user 64 to compete against other bidders or gamblers respectively. In one embodiment of the present invention, the plurality of launch preferences 158 can include a preference that if an auto participate launch is enabled it will not be

- 5 launched if the session device in which the session client 22 operates is not located near the body since there is no one to participate unless an auto bid program has been loaded and turned on. Alternatively, the plurality of launch preferences 158 can include a preference that if the session device in which the session client 22 operates is not connected to the online session 80 when it had expired, the session client 22, 10 through the browser 148, automatically goes to the site and retrieves the final results. Similarly, the plurality of launch preferences 158 can include automatically retrieving the final results of the online session 80 in the case an agent was bidding on the buyer's behalf.

- The plurality of alert preferences 160 of the browser 148 preferably includes 15 alert information programmable by the online account user 64. For example, the plurality of alert preferences 160 can include a "user aware alert" that would notify the user that the session client 22 was able to take action on the auctioned item or the gambling event and not just in process of linking to the item or event. In one embodiment, the plurality of alert preferences 160 can include an entry notification 20 alert that would notify the online account user 64 when a new entry for the online session 80 in which the online account user 64 is participating is received. For example, an alert can be generated when the bid price changes in an online auction session. The alert preferably includes a data message with the new bid price and the

incremental change. Alternatively, a particular level of incremental change could trigger an alert. In another embodiment, the plurality of alert preferences **160** can include an entry deletion alert that would notify the online account user **64** when an unread entry for the online session **80** in which the online account user **64** is participating is to be deleted from the memory. Alternatively, the plurality of alert preferences **160** can include a preference that no alert can be sent when a new entry is received and stored in the memory. It will be appreciated by one of ordinary skill in the art that other alerting schemes are within the scope of the present invention.

The plurality of current sessions **150** preferably includes an identification of all online sessions for which the session client **22** is currently participating. The plurality of current sessions **150**, for example, can be any of the plurality of online sessions **54** such as the online session **80**, the first online session **82** and/or the second online session **84** of FIG. 2.

The plurality of transfer clients' profiles **156** preferably includes the client profile **246** for each of the plurality of session clients **12** for which the session client **22** can transfer the plurality of session information **182** as required and/or desired. The client profile **246** can, for example, include the connection type (wide area network, short range wireless, infrared data association (IrDA), Universal Serial Bus (USB), or serial). If a wide or local area network was used for communication, the client profile **246** can further include routing information that can be converted to an IPv4 / MAC or IPv6 address. A user friendly name such as URL, Uniform Resource Identifiers (URI), phone number or other where a Domain Name Server (DNS) can be used to access a database to obtain the routable information (IP addressing).

FIG. 9 illustrates the plurality of client data **46** included within the session client **22** of FIG. 8. It will be appreciated by one of ordinary skill in the art that the plurality of client data **46** as illustrated in FIG. 9 can be the first client data **50** or the second client data **52**. As illustrated, the plurality of client data **46** preferably includes a client version identifier **162**, a current account identifier **164**, an authentication key **166**, a plurality of user preferences **168**, and a plurality of current session data **170**. It will be appreciated by one of ordinary skill in the art that the plurality of client data **46** can include any of the client data mentioned herein or an equivalent.

The client version identifier **162** is preferably the name and version or other similar indication of the session client **22** being used. The current account identifier **164** is preferably a user name or other identification of the online account user **64** currently using the session client **22**. The authentication key **166** preferably includes a code that is used to authenticate the online account user **64** to the online communication system **10**. For example, the authentication key **166** can be derived from a password known only to the online account user **64** and the online communication system **10**.

The plurality of user preferences **168** defines certain attributes settable by the account user **42** for communicating within the plurality of online sessions **54** using the session client **22**. The plurality of user preferences **168**, for example, can include text font attributes **176**, filter settings **172**, blocking settings, screen names per account identifier, alert settings per screen name **174**, buddy list groups, electronic mailboxes, electronic voice mail, and parental control settings. It will be appreciated by one of ordinary skill in the art that the plurality of user preferences **168**, in accordance with

the present invention, can include any of those preferences mentioned herein or an equivalent.

In a preferred embodiment of the present invention, the plurality of user preferences **168** includes a plurality of Internet cookies **178**. The session client **22** receives each of the plurality of Internet cookies **178**, which is essentially a tagged string of text containing the user's preferences, from an associated one of the plurality of online servers **14**.

The plurality of current session data **170** contains information relating to each of the plurality of online sessions **54** for which the account user **42** is currently participating, has previously participated, or plans to participate in, using the session client **22**. The plurality of current session data **170** preferably includes a session server identification **180** and a plurality of session information **182** for each online session **80** stored within the session client **22**. For example, a first session server identification **184** and a plurality of first session information **186** are stored within the plurality of current session data **170** for a first current session **188**. Similarly, a second session server identification **190** and a plurality of second session information **192** for a second current session **194** are stored within the plurality of current session data **170**. The session server identification **180**, such as the first session server identification **184** and the second session server identification **190** can be, for example, a unique selective call address in a wireless messaging system. Alternatively, the session server identification **180** can be an IP address, or an IP address and associated number of the port assigned to the online server **34** associated with the online session **80**. It will be appreciated by one of ordinary skill in the art

that the session server identification **180** can be one mentioned herein or an equivalent. The server identification **180** enables the communication between the session client **22** and the online server **34** hosting the online session **80**. Similar to that illustrated in FIG. 4, for each online session **80** included within the plurality of

5 current session data **170**, the session client **22** preferably stores the plurality of session information **182** such as the session identifier **86**, the session priority **88**, the plurality of session preferences **90**, the plurality of session participants **92**, the plurality of session data **94**, the session history **96**, and the session Internet cookie **97** as illustrated and described previously in FIG. 4. It will be appreciated by one of ordinary skill in

10 the art that the plurality of session information **182**, in accordance with the present invention, can include any of the session information mentioned herein or an equivalent.

FIG. 10 is an electronic block diagram of one embodiment of a session device in which the session client **22** of FIG. 8 operates. Specifically, FIG. 10 illustrates a

15 fixed network device **196**. The fixed network device **196** can operate for example on a local area network (LAN) or a wide area network (WAN) or a combination of both. The fixed network device **196** can be one of a plurality of spatially co-located computers which are typically located within a room, building or campus of buildings and are sharing common resources and communicating with each other on a computer

20 network in a manner well known to one of ordinary skill in the art. Typical resources shared are files on a file server, printers on a print server, and electronic message (email) services on an email server. The fixed network device **196** can operate on a network that uses a physical network such as ARCNET, Ethernet, Token-ring, Local

Talk or other network media to connect the computers, which represent wired network nodes into the network. The fixed network device **196** can operate on a LAN that employs any one of a number of networking protocols, such as TCP/IP (Transmission Control Protocol/Internet Protocol), AppleTalk™, IPX/SPX (Inter-Packet

- 5 Exchange/Sequential Packet Exchange), Net BIOS (Network Basic Input Output System) or any other packet structures to enable the communication among the devices and/or between the devices and the shared resources. Further the fixed network device **196** can operate on a WAN that uses a different physical network media such as X.25, Frame Relay, ISDN, Modem dial-up or other media to connect
- 10 other computers or other local area networks. In the following description, the term “fixed network device” includes any of the session devices operating as described above or an equivalent.

- As illustrated, the fixed network device **196** comprises a timing clock **198**, a central processing unit **200**, an electronic memory preferably in the form of a random
- 15 access memory (RAM) **202** and/or a read only memory (ROM) **204**, and a mass storage element (e.g., a disk drive or the like) **206**. In one embodiment, the fixed network device **196** includes a memory interconnect **208** for operatively connecting a memory storage device **210** to the fixed network device **196**. The memory interconnect **208** can, for example, comprise a structure for physically engaging
- 20 external contacts on the memory storage device **210** so that the memory storage device **210** is directly connected to the fixed network device **196**. It will be appreciated by one of ordinary skill in the art that the memory interconnect **208** can also be a wireless connection such as an infrared, Bluetooth or radio frequency

interface. When the memory interconnect **208** is connected to the memory storage device **210**, the fixed network device **196** can access a plurality of memory information such as the plurality of client data **46** from the memory storage device **210**.

- 5 The fixed network device **196** further preferably comprises a display driver **212**, a general I/O interface or data port **214**, and a user interface port **216** that accommodates a user interface **218** including any number of input means for general information entry. In the preferred embodiment, the user interface **218**, e.g., a keyboard **220**, a "mouse," **222**, a pen or puck activated tablet (not shown), a trackball
- 10 **224**, an audio activated command recognition processor **226**, or the like, allows a device user to enter and manipulate information using a user input **228**. After information is entered, it can be communicated to a wired communication system **230** via a conventional modem **232** or the like. Preferably, the fixed network device **196** also includes an Ethernet connection **234** for communicating to the wired
- 15 communication system **230** or for communicating through either a conventional cable modem **236** to a cable headend, or a (Digital Subscriber Line) DSL connection **238** to the wired communication system **230**. The fixed network device **196** can be changed from an active to an inactive state or from an inactive state to an active state through the user input **228** to a power circuit **240**. The power circuit **240** can be operated
- 20 manually via the user input **228** directly to the power circuit **240**, the user input **228** to the user interface **218**, or alternatively automatically via the programming of the CPU **200**.

In a preferred embodiment of the present invention, the fixed network device **196** of FIG. **10** includes a fixed session client **242**. It will be appreciated by one of ordinary skill in the art that the fixed session client **242** can be the first session client **18**, the second session client **20**, or any other of the plurality of session clients **12** of FIG. **1** with a structure as illustrated in FIG. **8**. The fixed network device **196** performs online session functions within the fixed session client **242** using the plurality of client data **46** stored in the electronic memory of the fixed network device **196**. The fixed session client **242** can be hard coded or programmed into the fixed network device **196** during manufacturing, can be programmed over-the-air upon customer subscription, or can be a downloadable application. It will be appreciated that other programming methods can be utilized for programming the fixed session client **242** into the fixed network device **196**. It will be further appreciated by one of ordinary skill in the art that the fixed session client **242** can be hardware circuitry within the fixed network device **196**.

Preferably the fixed session client **242** automatically updates a CRT **244** when a new session entry has been sent or received by sending a command to the display driver **212**. This allows the session history **96** to be updated while the device user is reading it without disturbing the CRT **244**. The fixed session client **242** uses the plurality of client data **46** stored in the electronic memory or stored in the memory storage device **210** to perform functions relating to the plurality of online sessions **54**. It will be appreciated by one of ordinary skill in the art that fixed networked devices having software-programming capabilities can include client data that is specialized and personalized such as the plurality of user preferences **168** including display

options and screens for each account user **42**, or similarly can include the plurality of session preferences **90** for each online session **80**. Alternatively, fixed networked devices that do not include software-programming capabilities can include the plurality of client data **46** including the plurality of user preferences **168** that are

5 standard, pre-defined display options and screens for the plurality of current sessions for which the fixed session client **242** is participating.

The plurality of user preferences **168** of the plurality of client data **46** used by the fixed session client **242** further includes various alert options. In one embodiment, the fixed session client **242** notifies the CPU **200** to send a command to

10 an alert circuit (not shown) when new session entries or event information is received and/or when the current time either equals an event time or is within a predetermined time differential of an event time. In another embodiment, the fixed session client **242** notifies the CPU **200** to send a command to the alert circuit when an unread session entry is to be deleted from the memory. Alternatively, no alert can be sent

15 when new session entries or event information is received and stored in the memory. It will be appreciated by one of ordinary skill in the art that other alerting schemes are within the scope of the present invention. Further, the CPU **200** can send a command to the alert circuit in response to the user input **228** to the user interface **218** through to the user interface port **216**, such as a device user depressing a button or series of

20 buttons, or in response to receipt of a message initiates an input signal to the fixed session client **242**. The fixed session client **242**, in response to the input signal, accesses the plurality of client data **46** stored in the electronic memory for use in operation of the fixed session client **242**.

Preferably, the fixed session client **242** includes the client profile **246**. The client profile **246** includes information regarding the capabilities and limitations of the fixed session client **242** and also of the fixed network device **196**. For example, the client profile **246** can include indication of the media supported by the fixed session client **242** (e.g. audio, video), indication of which features are supported by the fixed session client **242**, device type, device display, device battery life, device battery capacity, device processing power, and access to alternate networks. It will be appreciated by one of ordinary skill in the art that the client profile **246** can include any of those mentioned above in any combination or an equivalent.

In accordance with the present invention, the fixed session client **242** includes software capability for transferring all or a portion of the plurality of client data **46** to one or more other session clients for use by the other session client to participate within one or more of the plurality of online sessions **54** within one or more of the plurality of online servers **14**. The fixed session client **242**, in accordance with the present invention, further includes software capability for receiving all or a portion of the plurality of client data **46** from at least one other session client to participate within one or more of the plurality of online sessions **54** within one or more of the plurality of online servers **14**. As illustrated in FIG. **10**, the software capability for transferring and/or the capability for receiving the plurality of client data **46** can be incorporated into the fixed session client **242**, or alternatively can be contained within a separate data transfer application **248**. The data transfer application **248**, for example can be a third party software add-on that is compatible with existing session client software applications (e.g. the fixed session client **242**) already programmed

into the fixed network device **196**. Maintaining the data transfer software on a separate data transfer application **248** minimizes incorporation timeframes and also the cost of upgrading the fixed network device **196** to include this feature.

FIG. 11 is an electronic block diagram of one embodiment of a session device in which the session client **22** of **FIG. 8** operates. Specifically, **FIG. 11** illustrates a mobile device **250**. It will be appreciated by one of ordinary skill in the art that the mobile device **250** in accordance with the present invention, can be a mobile cellular telephone, a mobile radio data terminal, a mobile cellular telephone having an attached data terminal, or a two way pager, such as the "Pagerwriter 2000X" manufactured by Motorola Inc. of Schaumburg, Illinois. In the following description, the term "mobile device" refers to any of the session devices mentioned above or an equivalent.

As illustrated in **FIG. 11**, the mobile device **250** includes a first antenna **252**, a second antenna **254**, a receiver **256**, a transmitter **258**, a clock **260**, a processor **262**, a device memory **264**, a device memory interconnect **266**, a device alert circuit **268**, a device display **270**, a device user interface **272** and a mobile session client **274**.

The first antenna **252** intercepts transmitted signals from a wireless communication system **276**. It will be appreciated by one of ordinary skill in the art that the wireless communication system **276**, in accordance with the present invention, can function utilizing any wireless radio frequency (RF) channel, for example, a one or two-way pager channel, a mobile cellular telephone channel, or a mobile radio channel. Similarly, it will be appreciated by one of ordinary skill in the art that the wireless communication system **276** can function utilizing other types of

communication channels such as infrared channels. In the following description, the term "wireless communication system" refers to any of the wireless communication systems mentioned above or an equivalent.

The first antenna **252** is coupled to the receiver **256**, which employs
5 conventional demodulation techniques for receiving the communication signals transmitted by the wireless communication system **276**. Coupled to the receiver **256**, is the processor **262** utilizing conventional signal-processing techniques for processing received messages. Preferably, the processor **262** is similar to the MC68328 micro-controller manufactured by Motorola, Inc. of Schaumburg, Illinois.
10 It will be appreciated by one of ordinary skill in the art that other similar processors can be utilized for the processor **262**, and that additional processors of the same or alternative type can be utilized as required to handle the processing requirements of the processor **262**. The processor **262** decodes an address in the demodulated data of the received message, compares the decoded address with one or more addresses **278**
15 stored in an address memory **280** of the device memory **264**; and when a match is detected, proceeds to process the remaining portion of the received message.

To perform the necessary functions of the mobile device **250**, the processor **262** is coupled to the device memory **264**, which preferably includes a random access memory (RAM), a read-only memory (ROM), and an electrically erasable
20 programmable read-only memory (EEPROM)(not shown). The device memory **264** includes the address memory **280**, a message memory **282**, and a client data memory **284**.

Once the processor **262** has processed a received message, it stores the decoded message in the message memory **282** of the device memory **278**. It will be appreciated by one of ordinary skill in the art that the message memory **282**, in accordance with the present invention, can be a voicemail box or a group of memory locations in a data storage device. In the following description, the term “message memory” refers to any of the memory means mentioned above or an equivalent. Preferably, when the received message is a message for participation in one of the plurality of online sessions **54**, for example the session entry **142**, the processor **262** stores the decoded message in the client data memory **284**.

In one embodiment, the mobile device **250** includes the device memory interconnect **266** for operatively connecting the memory storage device **210** to the mobile device **250**. The device memory interconnect **266** can, for example, comprise a structure for physically engaging external contacts on the memory storage device **210** so that the memory storage device **210** is directly connected to the mobile device **250**. It will be appreciated by one of ordinary skill in the art that the device memory interconnect **266** can also be a wireless connection such as an infrared, Bluetooth or radio frequency interface. When the device memory interconnect **266** is connected to the memory storage device **210**, the mobile device **250** can access a plurality of memory information such as the plurality of client data **46** from the memory storage device **210**.

The client data memory **284** includes the plurality of client data **46** as described previously in FIG. 9. The client data memory **284** includes a memory slot **286** for each online session **80** in which the mobile device **250** has subscribed. The memory slot

286, in accordance with the present invention, includes the plurality of session data as illustrated in FIG. 9 and FIGs. 4-7. The plurality of session entries 140 associated with the online session 80 is stored together in chronological order in the memory slot 286 similar to the session history 96 of FIG. 7. The memory slot 286 is preferably

- 5 allocated a fixed amount of memory for storing associated plurality of session data. The memory slot 286 holds multiple session entries in a single memory slot. Any session entries received for the online session 80 along with its associated session information is appended at the end of the plurality of session entries already in the memory slot 286. If the amount of allocated memory for the memory slot 286 is
- 10 exceeded, the older session entries are deleted. It will be appreciated by one of ordinary skill in the art that, in accordance with the present invention, the client data memory 284 and associated operation herein described, in accordance with the present invention, can be included in the fixed network device 196 of FIG. 10, a cable box as illustrated in FIG. 12, or any other session device in which the session client 22
- 15 operates.

- Upon receipt and processing of a message, the processor 262 preferably generates a command signal to the device alert circuit 268 as a notification that the message has been received and stored. The device alert circuit 268 can include a speaker (not shown) with associated speaker drive circuitry capable of playing
- 20 melodies and other audible alerts, a vibrator (not shown) with associated vibrator drive circuitry capable of producing a physical vibration, or one or more LEDs (not shown) with associated LED drive circuitry capable of producing a visual alert. It will be appreciated by one of ordinary skill in the art that other similar alerting means as

well as any combination of the audible, vibratory, and visual alert outputs described can be used for the device alert circuit **268**.

Upon receipt and processing of a message, the processor **262** preferably also generates a command signal to the device display **270** to generate a visual notification of the receipt and storage of the message. When the device display **270** receives the command signal from the processor **262** that the message has been received and stored in the device memory **264**, a message indication is displayed. The message indication, for example can be the activation of one of a plurality of message icons on the device display **270**. The device display **270** can be, for example, a liquid crystal display utilized to display text. It will be appreciated by one of ordinary skill in the art that other similar displays such as cathode ray tube displays can be utilized for the device display **270**.

The mobile device **250** preferably further includes the clock **260**. The clock **260** provides timing for the processor **262**. The clock **260** can include the current time for use in the operation of the mobile device **250**. The clock **260** also provides a source for timing of feature enhancements such as active and inactive periods of operation or periods of alerting.

In a preferred embodiment, the mobile device **250** includes the mobile session client **274**. It will be appreciated by one of ordinary skill in the art that the mobile session client **274** can be the first session client **18**, the second session client **20**, or any other of the plurality of session clients **12** of FIG. 1. The mobile session client **274** performs session operation functions within the mobile device **250** using the plurality of client data **46** stored in the client data memory **284**. The mobile session

client **274** can be hard coded or programmed into the mobile device **250** during manufacturing, can be programmed over-the-air upon customer subscription, or can be a downloadable application. It will be appreciated that other programming methods can be utilized for programming the mobile session client **274** into the

5 mobile device **250**. It will be further appreciated by one of ordinary skill in the art that the mobile session client **274** can be hardware circuitry within the mobile device **250**. Preferably the mobile session client **274** automatically updates the device display **270** when a new session entry has been sent or received. This allows the session history **96** to be updated while the account user **42** is reading it without

10 disturbing the device display **270**. The mobile session client **274** uses the plurality of client data **46** stored in the electronic memory or stored in the memory storage device **210** to perform functions relating to various received and/or sent session entries. It will be appreciated by one of ordinary skill in the art that mobile devices having software-programming capabilities can include specialized and personalized display

15 options and screens for each online session **80**. Alternatively, mobile devices that do not include software-programming capabilities can include standard, pre-defined display options and screens for the plurality of online sessions **54**. In accordance with the present invention, the display options for the plurality of online sessions **54** in which the mobile session client **274** within the mobile device **250** is participating can

20 be included in the plurality of session preferences **90** for each online session **80** or alternately, the display options can be stored independently within the plurality of user preferences **168** of the plurality of client data **46**.

The mobile session client 274 further operates using various alert options. In one embodiment, the mobile session client 274 notifies the processor 262 to send a command to the device alert circuit 268 when a new session entry is added to the memory slot 286 of the client data memory 284 for the online session 80 or when the current time is an event time or within a predetermined window of an event time. In another embodiment, the mobile session client 274 notifies the processor 262 to send a command to the device alert circuit 268 when an unread session entry is to be deleted from the memory slot 286. Alternatively, no alert can be sent when a new session entry is received and stored in the client data memory 284 and/or when the current time is an event time. It will be appreciated by one of ordinary skill in the art that other alerting schemes are within the scope of the present invention. In accordance with the present invention, the alert options for the plurality of current sessions 150 in which the mobile session client 274 within the mobile device 250 is participating can be included in the plurality of session preferences 90 for each online session 80 or alternately, the alert options can be stored independently within the plurality of user preferences 168 of the plurality of client data 46.

In accordance with the present invention, the mobile session client 274 includes software capability for transferring all or a portion of the plurality of client data 46 to at least one other session client for use by the other session client to participate within one or more of the plurality of current sessions 150. The mobile session client 274, in accordance with the present invention, further includes software capability for receiving all or a portion of the plurality of client data 46 from another session client to participate within one or more of the plurality of online sessions 54.

As illustrated in FIG. 11, the software capability for transferring and receiving client data can be incorporated into the mobile session client **274** (not shown) or alternatively contained within a separate data transfer application **248**. The data transfer application **248**, for example can be a third party software add-on that is compatible with existing online software applications (e.g. the mobile session client **274**) already programmed into the mobile device **250**. Maintaining the data transfer software on a separate data transfer application **248** minimizes incorporation timeframes and also the cost of upgrading a mobile device to include this feature.

Preferably, the device user interface **272** is coupled to the processor **262**. The device user interface **272** can be one or more buttons used to generate a button press, a series of button presses, a voice response from the device user, or some other similar method of manual response initiated by the device user (such as the online account user **64**) of the mobile device **250**. The processor **262**, in response to the device user interface **272**, such as a device user depressing a button or series of buttons, or in response to receipt of a session message, initiates an input signal to the mobile session client **274**. The mobile session client **272**, in response to the user input signal, accesses the plurality of client data **46** in the client data memory **284** for use in operation of the mobile session client **274**.

Preferably, the mobile session client **274** includes the client profile **246**. The client profile **246** includes information regarding the capabilities and limitations of the mobile session client **274** and also of the mobile device **250**. For example, the client profile **246** can include indication of the media supported by the mobile session client **274** (e.g. audio, video), indication of which features are supported by the mobile

session client **274**, device type, device protocol usage, device display, device battery life, device battery capacity, device processing power, and access to alternate networks. It will be appreciated by one of ordinary skill in the art that the client profile **246** can include any of those mentioned above in any combination or an equivalent.

The transmitter **258** is coupled to the processor **262** and is responsive to commands from the processor **262**. When the transmitter **258** receives a command from the processor **262**, the transmitter **258** sends a signal via the second antenna **254** to the wireless communication system **276**.

In an alternative embodiment (not shown), the mobile device **250** includes one antenna performing the functionality of the first antenna **252** and the second antenna **254**. Further, the mobile device **250** alternatively includes a transceiver circuit performing the functionality of the receiver **256** and the transmitter **258**. It will be appreciated by one of ordinary skill in the art that other similar electronic block diagrams of the same or alternate type can be utilized for the mobile device **250** to handle the requirements of the mobile device **250**.

The mobile device **250** can be changed from an active state to an inactive state or from an inactive state to an active state through a user input to a power circuit **288**. The power circuit **288** can be operated manually via the user input to the power circuit **288**, the user input to the device user interface **272**, or alternatively automatically via the programming of the processor **262**.

FIG. **12** is an electronic block diagram of one embodiment of a session device in which the session client **22** of FIG. **8** operates. Specifically, FIG. **12** illustrates an

interactive broadcast receiver such as a cable box **290**. The cable box **290** preferably allows network operators to deploy a wide range of interactive television broadcast services and applications on their networks. Further the cable box **290** preferably offers cable operators a combined, all-in-one, hardware and software solution for

5 deploying interactive television services on their networks, thereby creating the ability for real time electronic message communication using television sets and networks.

As illustrated in FIG. **12**, the cable box **290** preferably includes a controller **292** for controlling the operation of the cable box **290**. Preferably, the controller **292** is similar to the MC68328 micro-controller manufactured by Motorola, Inc. of

10 Schaumburg, Illinois. It will be appreciated by one of ordinary skill in the art that other similar processors can be utilized for the controller **292**, and that additional processors of the same or alternative type can be utilized as required to handle the processing requirements of the controller **292**. Preferably, the controller **292** is programmed to function with a cable session client **294**. The cable session client **294**,

15 in accordance with the present invention, operates similarly to the fixed session client **242** of FIG. **10** and the mobile session client **274** of FIG. **11** as described above. It will be appreciated by one of ordinary skill in the art that the cable session client **294** illustrated in FIG. **12** can be the first session client **18**, the second session client **20**, or any other of the plurality of session clients **12** of FIG. **1**.

20 In accordance with the present invention, the cable session client **294** includes software capability for transferring all or a portion of the plurality of client data **46** to at least one other session client for use by the other session client to participate within one or more of the plurality of current sessions **150**. The cable session client **294**

further includes software capability for receiving all or a portion of the plurality of client data **46** from another session client to participate within one or more of the plurality of online sessions **54**. As illustrated in FIG. **12**, the software capability for transferring and receiving client data can be incorporated into the cable session client

- 5 **294** (not shown) or alternatively contained within a separate data transfer application **248**. The data transfer application **248**, for example can be a third party software add-on that is compatible with existing online software applications (e.g. the cable session client **294**) already programmed into the cable box **290**. Maintaining the data transfer software on a separate data transfer application **248** minimizes incorporation
- 10 timeframes and also the cost of upgrading a device to include this feature.

Preferably, the cable session client **294** includes the client profile **246**. The client profile **246** includes information regarding the capabilities and limitations of the cable session client **294** and of the cable box **290**. For example, the client profile **246** can include indication of the media supported by the cable session client **294** (e.g.

- 15 audio, video), indication of which features are supported by the cable session client **294**, device type, device protocol usage, device display, device battery life, device battery capacity, device processing power, and access to alternate networks. It will be appreciated by one of ordinary skill in the art that the client profile **246** can include any of those mentioned above in any combination or an equivalent.

- 20 The cable box **290** further includes an up/down converter **296** coupled to the controller **292** for communicating with a cable headend. To perform the necessary functions of the cable box **290**, the controller **292** is further coupled to a cable box memory **298**, which preferably includes a cable box random access memory (RAM)

300, a cable box read-only memory (ROM) **302**, and an electrically erasable programmable read-only memory (EEPROM)(not shown). The cable box memory **298** of the cable box **290** preferably includes the client data memory **284** as previously described and illustrated in FIG. **11**.

- 5 In one embodiment, the cable box **290** includes a cable box memory interconnect **304** for operatively connecting the memory storage device **58** to the cable box **136**. The cable box memory interconnect **304** can, for example, comprise a structure for physically engaging external contacts on the memory storage device **210** so that the memory storage device **210** is directly connected to the cable box **290**. It
- 10 will be appreciated by one of ordinary skill in the art that the cable box memory interconnect **304** can also be a wireless connection such as an infrared, Bluetooth or radio frequency interface. When cable box memory interconnect **304** is connected to the memory storage device **210**, the cable box **290** can access a plurality of memory information such as the plurality of client data **46** from the memory storage device
- 15 **210**.

- Further coupled to the controller **292** is a first cable box I/O **306** for driving a remote control transceiver **308** and further for driving a radio frequency transceiver **310** connected to a cable box antenna **312**. A second cable box I/O **314** for inputs from a user input via a cable box user interface **316** is further coupled to the controller
- 20 **292**. Also coupled to the controller **292** are an audio driver **318** and a radio frequency/video driver **320** for communicating with a television **322**.

 The cable box **290** can be changed from an active state to an inactive state or from an inactive state to an active state through a user input to a cable box power

circuit **324**. The cable box power circuit **324** can be operated manually via the user input to the cable box power circuit **324**, the user input to the cable box user interface **316** or alternatively automatically via the programming of the controller **292**.

FIG. **13** is an electronic block diagram of one embodiment of the online communication system of FIG. **1**. Specifically, the online communication system **10** as illustrated in FIG. **13** includes, an Internet server **326**, the plurality of session clients **12** within a plurality of mobile devices **328**, and the wireless communication system **276**.

The wireless communication system **276**, as illustrated in FIG. **13** includes a message input device for initiating messages into the wireless communication system **276**. The message input device can be, for example, a telephone **330**, a computer **332**, a desktop messaging unit **334**, or the Internet server **326** connected through a conventional public switched telephone network (PSTN) **336** through a plurality of telephone links **338** to a wireless system controller **340**. The telephone links **338**, for example, can be a plurality of twisted wire pairs, a fiber optic cable, or a multiplexed trunk line.

The wireless system controller **340** is coupled to and oversees the operation of at least one radio frequency (RF) transmitter **342** and at least one radio frequency (RF) receiver **344** through one or more communication links **346**. The communication links **346** typically are twisted pair telephone wires, and additionally can include radio frequency (RF), microwave, or other communication links. The RF transmitter **342** and the RF receiver **344** typically are used with message store and forward stations that encode and decode inbound and outbound messages into formats that are

compatible with landline message switched computers and personal radio addressing requirements, such as cellular messages, short messaging service, or paging protocols. The wireless system controller **340** can also function to encode and decode wireless messages that are transmitted to or received by the RF transmitter **342** or the RF receiver **344**. Telephony signals are typically transmitted to and received from the wireless system controller **340** by telephone sets such as the telephone **330** or a mobile device. The wireless system controller **340** encodes and schedules outbound messages such as a downlink message **348**. The wireless system controller **340** then transmits the encoded outbound messages through the RF transmitter **342** via a transmit antenna **350** to the plurality of mobile devices **328** such as the mobile device **250** of FIG. **11** on at least one outbound radio frequency (RF) channel **352**. The plurality of mobile devices **328**, for example, includes a first mobile device **354**, a second mobile device **356**, and a third mobile device **358** each communicating through a wireless connection such as the outbound RF channel **352** and an inbound RF channel **360**. The downlink message **348** can be, for example, the plurality of client data **46**, the session entry **142**, the plurality of session information **182**, or any other of similar data. Similarly, the wireless system controller **340** receives and decodes inbound messages such as an uplink message **362** received by the RF receiver **344** via a receive antenna **364** on at least one inbound radio frequency (RF) channel **360** from one of the plurality of mobile devices **328**. The uplink message **362** can be, for example, the plurality of client data **46**, the session entry **142**, the plurality of session information **182**, or any other of similar data.

Each of the plurality of mobile devices **328** assigned for use with the wireless communication system **276** has an address or identity assigned thereto which is a unique selective call address in the wireless communication system **276**. For example, the first mobile device **354** has a first address **366**, the second mobile device **356** has a second address **368**, and the third mobile device **358** has a third address **370**. It will be appreciated by one of ordinary skill in the art that other mobile devices assigned for use with the wireless communication system **276** have an address assigned thereto which is a unique selective call address in the wireless communication system **276**. The address enables the transmission of the downlink message **348** from the wireless system controller **340** only to the mobile device having the address, and identifies the messages and responses received at the wireless system controller **340** from the mobile device with the address. In one embodiment, each of the plurality of mobile devices **328** also has a pin number assigned thereto, the pin number being associated with a telephone number within the PSTN **336**. A list of the assigned addresses and correlated telephone numbers for each of the plurality of mobile devices **328** is stored in the wireless system controller **340** in the form of a subscriber database **372**.

Preferably, at least one session client operates within a mobile device. For example, as illustrated in FIG. 13, the first session client **18** operates within the first mobile device **354** and the second session client **20** operates within the second mobile device **356**. Similarly, a plurality of session clients can operate within the same mobile device. For example, a third session client **374** and a fourth messaging client **376** operate within the third mobile device **358**. It will be appreciated by one of

ordinary skill in the art that, in accordance with the present invention, a mobile device can include no session client, one session client, or a plurality of session clients.

In one embodiment of the present invention, the Internet server **326** is coupled to the wireless system controller **340** of the wireless communication system **276**. The

5 Internet server **326** provides a means for real time electronic communication between the plurality of mobile devices **328** and the plurality of online servers **14** via the Internet computer network **16**. The Internet server **326**, for example, receives a request and can in response to such receipt, sends a response, both via the wireless system controller **340**. The wireless system controller **340** then routes the response to
10 the requesting device which can be a message input device, such as the telephone **330**, the computer **332**, or the desktop messaging unit **334**, or alternatively can be an individual or one of the plurality of mobile devices **328**. In the following description, the term “requester” refers to any of the requesting devices mentioned above or an equivalent.

15 Preferably, the Internet server **326** includes a server address **378**, which is a unique selective call address in the wireless communication system **276**. The server address **378** enables the transmission, via the inbound RF channel **360**, to the Internet server **326** of various real time electronic communications. The Internet server **326** similarly sends real time electronic communications to the plurality of mobile devices
20 **328** via the outbound RF channel **352**. Furthermore, the Internet server **326** can also have a pin number assigned thereto, the pin number being associated with a telephone number within the PSTN **336**. The server address **378** and correlated telephone

number is stored in the in the subscriber database **372** of the wireless system controller **340**.

The coupling of the Internet server **326** to the wireless communication system **276** enhances the operation of the online communication system **10** by adding intelligence for multiple mobile devices to communicate in substantially real time with multiple online servers. The Internet server **326** interactively manages the messaging traffic associated with multiple online sessions in an efficient manner.

FIG. **14** is an electronic block diagram of one embodiment of the online communication system of FIG. **1**. Specifically, FIG. **14** illustrates an embodiment of the present invention in which the online communication system **10** includes the wired communication system **230** of FIG. **10**. The wired communication system **230**, for example, can include a LAN **380** (local area network), a WAN **382** (wide area network), or a combination of LAN **380** and WAN **382** networks. It will be appreciated that while only a single LAN **380** and a single WAN **382** are shown, multiple LAN **380** networks and/or WAN **382** networks can be interconnected in a manner well known to one of ordinary skill in the art for the transfer of electronic communication such as electronic mail (email), and real time electronic messaging (i.e.: instant messaging and chat messaging) including the plurality of session entries **140** and other of the plurality of client data **46**.

The general function and operation of the LAN **380** is one of allowing spatially co-located computers which are typically located within a room, building or campus of buildings to communicate with each other and/or share common resources on a computer network in a manner well known to one of ordinary skill in the art. The

spatially co-located computers are represented pictorially in FIG. 14 as a plurality of network devices, such as the fixed network device 196 of FIG. 10, three of which are shown by example. (a first network device 384, a second network device 386, and a third network device 388) Each of the plurality of network devices communicates using a network connection 390. Preferably, at least one session client operates within a network device. For example, as illustrated in FIG. 14, the first session client 18 operates within the first network device 384 and the second messaging client 20 operates within the second network device 386. Similarly, a plurality of session clients can operate within the same network device. For example, the third session client 374 and the fourth session client 376 operate within the third network device 388. It will be appreciated by one of ordinary skill in the art that, in accordance with the present invention, a network device can include no session client, one session client, or a plurality of session clients.

Typical resources shared on the LAN 380 through a LAN server 392 are files on a file server, printers on a print server, electronic message (email) services on an email server, and Internet connection services on an Internet server. The LAN 380 uses a physical network such as ARCNET, Ethernet, Token-ring, Local Talk or other network media to connect the computers, which represent wired network nodes into the network. The LAN 380 can employ any one of a number of networking protocols, such as TCP/IP (Transmission Control Protocol/Internet Protocol), AppleTalk™, IPX/SPX (Inter-Packet Exchange/Sequential Packet Exchange), Net BIOS (Network Basic Input Output System) or any other packet structures to enable the communication between clients and the server. In the following description, the term

“local area network” refers to a network utilizing any of the networking protocols mentioned above or an equivalent. The LAN 380 can also use routers (not shown) to subnet the LAN 380 organizationally or physically. In this context, the definition of the LAN 380 as described herein refers to a geographic locality of computers and the

5 type of wired media used to interconnect the computers for communication.

The general function and operation of the WAN 382 is also one of allowing computers to share common resources. However, in this context the definition used herein is one where the computers are not spatially co-located. The typical resources shared are similar to, if not the same, as found in the LAN 380. However, the WAN

10 382 uses a different physical network media such as X.25, Frame Relay, ISDN, Modem dial-up or other media to connect other computers or other local area networks to the WAN 382 network. The WAN 382, for example, can include a number of well-known private wide area networks, one (394) of which is shown by example; and public wide area networks, one (396) of which is show by example,

15 such as CompuServe™, America Online™ (AOL), the MIT computer network, the Motorola™ computer network and Prodigy™. In the following description, the term “wide area network” refers to any of the networks mentioned above or an equivalent. The WAN 382 described above can operate independently, or can be interconnected through the Internet computer network 16. Likewise, the LAN 380 can also be

20 interconnected to the WAN 382 through the Internet computer network 16, as shown, in a manner well known to one of ordinary skill in the art.

FIG. 15 is an electronic block diagram of one embodiment of the online communication system 10 of FIG. 1. Specifically, FIG. 15 illustrates an alternate

embodiment of the present invention in which the online communication system **10** includes a broadcast communication system **398**.

The broadcast communication system **398** preferably includes a cable headend **400**, a network PSTN **402**, and a plurality of cable boxes, such as the cable box **290** of

FIG. **12**, three of which are shown by way of example. (a first cable box **404**, a second cable box **406**, and a third cable box **408**. Each of the plurality of cable boxes

communicates within the broadcast communication system **398** via a wired

connection **410**. Preferably, at least one session client operates within a cable box.

For example, as illustrated in FIG. **15**, the first session client **18** operates within the

first cable box **404** and the second session client **20** operates within the second cable

box **406**. Similarly, a plurality of session clients can operate within the same cable

box. For example, the third session client **374** and the fourth session client **376**

operate within the third cable box **408**. It will be appreciated by one of ordinary skill

in the art that, in accordance with the present invention, a cable box can include no

session client, one session client, or a plurality of session clients.

The cable headend **400** is coupled to the first cable box **404**, the second cable box **406**, the third cable box **408**, the network PSTN **402**, and, in one embodiment, the

Internet computer network **16**. The cable headend **400** enables operators to deliver services such as conventional video and audio broadcasting, near video on demand

(NVOD), video on demand (VOD), pay television, advertising, information,

interactive shopping and more. The cable headend **400** preferably offer functions

such as MPEG-2/DVB (Moving Picture Experts Group – 2/Digital Video

Broadcasting) encoding of local and non-compressed programs, insertion of local

advertising and events data insertion, conditional access (CA) scrambling, interactive services, and monitoring and control of the entire network. At the multiplexing stage, broadcasters can create program bouquets and add PSI/SI information (Program Specific Information (PSI)/specific information (SI)) before the outgoing transport stream is delivered to a conditional access (CA) system for scrambling. Following processing, transport streams are modulated and then transmitted to the cable headend 400 via telecom networks, terrestrial or satellite systems.

In one embodiment of the present invention, the Internet computer network 16 is coupled to the cable headend 400 of the broadcast communication system 398. The coupling of the cable headend 400 to the Internet computer network 16 provides a means for real time electronic communication between the cable boxes and the plurality of online servers 14.

FIG. 16 is an electronic block diagram illustrating an alternative embodiment of the online communication system 10 in accordance with the present invention. As illustrated, the online communication system 10 preferably includes a first communication system 412 having a first plurality of session clients 414, and a second communication system 416 having a second plurality of session clients 418. Preferably, the first communication system 412 and the second communication system 416 are coupled to the Internet computer network 16. It will be appreciated by one of ordinary skill in the art that while only two communications systems are shown by way of example, multiple communication systems can be interconnected in a manner well known to one of ordinary skill in the art for the transfer of electronic communication such as the plurality of client data 46 and the plurality of session

information **182** to the first plurality of session clients **414** and the second plurality of session clients **418**.

It will be appreciated by one of ordinary skill in the art that, in accordance with the present invention, the first communication system **412** and the second communication system **416** can be the wireless communication system **276** of FIG. **13**, the wired communication system **230** of FIG. **14**, the broadcast communication system **398** of FIG. **15** or any other equivalent system. Further, in accordance with the present invention, the online communication system **10** can include a plurality of wireless communication systems, a plurality of wired communication systems, or any combination thereof. Similarly, each session client of the first plurality of session clients **414** and the second plurality of session clients **418** can operate within the mobile device **250** of FIG. **11**, the fixed network device **196** of FIG. **10**, or the cable box **290** of FIG. **12**.

FIG. **17** is a flowchart illustrating the operation of the online communication system **10** in accordance with the preferred embodiment of the present invention. Beginning with Step **420**, the transfer clients' profiles **156** for the current sessions **150** are stored in the first session client **18**. The first session client **18**, for example, can be operating on a first session device such as the first mobile device **354** of FIG. **13**, the first network device **384** of FIG. **14**, the first cable box of FIG. **15**, or an equivalent. Next, in Step **422**, the first session device participates in one or more online sessions of the current sessions **150** such as the first current session **188**, the second current session **194** or any other online session **80**. For example, the online account user **64** can use the first session client **18** to participate in an online gambling event or an

online auction event via one or more of the plurality of online servers **14**. The first session client **18** operates using the first communication connection **32** and accumulates the plurality of session information **182** for each online session **80** for which the first session client **18** is participating. Next, in Step **424**, the process

5 determines whether to activate a session transfer. A session transfer, in accordance with the present invention, is the capability for the online account user **64** to change session communication means within the online communication system **10** from the first session client **18** to the second session client **20**. For example, when the online account user **64** establishes the first communication connection **32** using the fixed

10 network device **196** and thereafter needs to become mobile, the online account user **64** can activate a transfer the first client data **50** including the plurality of current session data **170** accumulated for the plurality of current sessions **150** to the second session client **20** which for example can operate on the mobile device **250**. When no data transfer is required or requested in Step **424**, the first communication connection **32** is

15 maintained in Step **422**, whereby the first session client **18** continues operating using the first communication connection **32** and accumulates the plurality of session information **182** for each online session **80** for which the first session client **18** is participating. In Step **426**, when a session transfer is activated in Step **424**, the session transfer is initialized.

20 FIG. **18** is a flowchart illustrating one embodiment of the operation of the online communication system **10** at Step **426** of FIG. **17** in accordance with the present invention. Starting at node A, at step **432**, the online account user **64** has decided to perform a session transfer from the first session client **18** to another session client of

the plurality of session clients **12**. For example, the online account user **64** can decide to perform a session transfer from the first session client **18** operating on the first network device **384** to another session device operating within the online communication system **10**. In Step **432**, the online account user **64** selects the second

5 session client **20** from among the plurality of transfer clients' profiles **156** of the first session client **18** stored in Step **420** of FIG. **17** to transfer the first client data **50** including the plurality of current session data **170** accumulated for the plurality of current sessions **150** to. Once the client profile **246** for a transfer device is selected from among the plurality of transfer clients' profiles **156** using the first session client

10 **18** on the first session device, in Step **434** a session transfer notification is sent from the first session client **18**. In one embodiment, the session transfer notification is sent from the first session client **18** to each online server **34** of the plurality of online servers **14** associated with each of the plurality of current sessions **150** informing the plurality of online servers **14** to pass the plurality of session information **182** for each

15 of online session **80** to the chosen transfer session client. For example, a session transfer notification is sent to the online server **34** hosting an auction event including a request for the auction session data **98** to be sent to the second session client **20**. Similarly, the session transfer notification can be sent to the online server **34** hosting a gambling event including a request for the gambling session data **118** to be sent to the

20 second session client **20**.

It will be appreciated by one of ordinary skill in the art that, alternatively, in accordance with the present invention, the session transfer notification can be sent directly to the second session client **20** from the first session client **18**, sent through

the plurality of online servers **14** to the second session client **20**, or any combination therein. For example, in Step **432**, the online account user **64** on the first session device in which the first session client **18** operates selects the desired transfer device. In step **434** the first session device sends the plurality of session information **182** for one or more online session **80** to the second session client **20** “through” the online server **34**. During step **436**, the second session client **20**, upon reception of the plurality of session information **182**, starts the second session client **20** on the second session device (receiving device) and begins a data transfer.

Next, in Step **436**, the data transfer application **248** is launched on the second session device. It will be appreciated by one of ordinary skill in the art that the data transfer application **248** can be an individual application or alternatively incorporated within the second session client **20** operating on the second session device. The process then continues at node B.

In utilizing the approach illustrated in FIG. **18**, the first session device can traverse the online server **34** that will provide a logical connection between the two session devices, an example is an instant messaging server that allows messaging information to be passed between two session devices. In this method the second session device will have to have username and password to access the online server **34** while the first session device will be able to determine when the second session device becomes available either through presence information or a periodic polling of the second session device. In a preferred method, the session devices performing the transfer are easily addressable and do not require intervention by the online server **34** to carry out the transfer of the plurality of session information **182**. It will be

appreciated by one of ordinary skill in the art that IPv6 or an equivalent provides this capability.

FIG. 19 is a flowchart illustrating an alternate embodiment of the operation of the online communication system **10** at Step **426** of FIG. **17** in accordance with the present invention. Beginning at node A, with Step **438**, the data transfer application **248** is launched on the second session device. It will be appreciated by one of ordinary skill in the art that the data transfer application **248** can be an individual application or alternatively incorporated within the second session client **20** operating on the second session device. Next, in Step **440**, the second session device, either via the data transfer application **248** or the second session client **20**, sends the session transfer notification to the first session client **18**. The session transfer notification preferably includes a request for the first session client **18** to transfer the first client data **50** including the plurality of current session data **170** accumulated for the plurality of current sessions **150** to the second session client **20**. Further, in Step **440**, the first session device, either via the first session client **18** or the data transfer application **248** of the first session device, receives the session transfer notification from the second session device. The process then continues at node B.

Referring back to FIG. **17**, in Step **428** the first session device and the second session device create a communication connection. It will be appreciated by one of ordinary skill in the art that the communication connection can be made using the data transfer application **248** of each of the first session device and the second session device, the first session client **18** and the second session client **20**, or any combination thereof. The connection can be either directly from the first session device to the

second session device, through the wide area network **382**, the local area network **380**, the Internet computer network **16**, short range wireless (e.g.: IrDA (Infrared data association standard), Bluetooth, USB (Universal Serial Bus), or Serial), the wireless communication system **276**, the wired communication system **230**, the broadcast
5 communication system **398**, or any combination thereof. It will be appreciated by one of ordinary skill in the art that the connection can be any of the connections described herein or an equivalent. During the setup process of Step **428**, both session devices can choose to authenticate and negotiate an encryption layer (not shown).

Next in Step **430**, the session transfer is accomplished. In Step **430**, the second
10 session device is provided with the necessary content including the plurality of current session data **170** accumulated for the plurality of current sessions **150** for the online account user **64** to continue with the plurality of current sessions **150** on the second session device. Depending upon how each online server **34** of the plurality of online servers **14** is configured, the transferable content can be as simple as an URL and
15 Cookie (updateable information maintained by the online server **34** on the session device) or can require additional information such as the auction session data **98** for an auction event or the gambling session data **118** for a gambling event. Each online session **80** is transferred from the first session device to the second session device. It will be appreciated by one of ordinary skill in the art that, optionally, in Step **430**, the
20 two session devices can perform an authentication / verification process and negotiate an encryption method (not shown) using, for example, the authentication key **166**.
The process then goes to node C.

FIG. 20 is a flowchart illustrating the operation of the online communication system 10 in accordance with the preferred embodiment of the present invention. Beginning with node C, the second session device has received the plurality of session information 182 required to seamlessly continue the plurality of online sessions 150.

- 5 At Step 442, the process determines whether an input by the online account user 64 has requested to go to an event site on the online server 34. Preferably, the event site is associated with at least one online session of the plurality of current sessions 150 in which the plurality of session information 182 was transferred to the second session device in Step 430 of FIG. 17. When a user input has been received, the process
- 10 continues to Step 460. When no user input has been received in Step 442, the process proceeds to Step 444 in which it is determined whether an asynchronous event notification has been received from the online server 34. Step 444 provides asynchronous external device event(s) to the session client 22 containing the online session application. For example, for an online auction session, the event can include
- 15 a higher bidder, a time remaining, an auction result(s), and a new auction with a similar item. For an online gambling session, the event can include a change in odds, an updated score, a time remaining, a change in position of players or animals on the event field, a late breaking news that would have a bearing on outcome, and a past session history performance. It will be appreciated by one of ordinary skill in the art
- 20 that the event can be any of those mentioned herein or an equivalent. Similarly, in Step 444, an expiring of event parameters (not shown) internally to the device can be an alternative to the asynchronous event notification from the online server 34.

When a server event notification has been detected in Step 444, the process continues with Step 446 in which it is determined whether user presence is required. When user presence is not required in Step 446, the process continues to Step 460. When user presence is required in Step 446, at node D and Step 448, the process

5 determines whether the online account user 64 is present. Preferably, the session client 22 determines if the online account user 64 is within close proximity of the session device and continues this process until the online account user 64 is within proximity of the session device. It will be appreciated by one of ordinary skill in the art that the user presence detection can be accomplished using several methods known

10 in the art. For example, the session device can one or more infrared sensor(s) for heat sensing; and using the output of one or more sensors to determine if the online account user 64 is in the vicinity of the session device. Similarly, the session device can include an audible sensor that can listen for the online account user's voice pattern to determine relative proximity to the session device. Alternatively, the

15 session device can use a proximity detector such as the detector described in United States Patent number 5,956,626, issued September 21, 1999, and titled "Wireless Communication Device having an Electromagnetic Wave Proximity Sensor" to Kaschke et al, which is assigned to the assignee of the present invention, and which is incorporated by reference herein. Alternatively, a detection device can be located on

20 the online account user's body including a pairing between this detection device and the session device communicating via short-range connectivity. The short-range connectivity can be Bluetooth and utilize the service discovery process of Bluetooth to determine when the online account user 64 is within proximity of the session device.

When the presence of the online account user **64** is detected in Step **448**, at node E, the process continues to Step **460**. When the presence of the online account user **64** is not detected in Step **448**, at node F and in Step **450**, the session device stores the event notification information in memory for later use once the user presence is

5 detected. For example, the session device stores the event notification information in the client data memory **284**. The process thereafter continues with Step **448** and node D checking periodically for presence of the online account user **64**.

Returning to Step **444**, when no server event notification is detected, in Step **452**, the session device determines if the current time has past the time of the event

10 start. For example, when the session device is the fixed network device **196**, the timing clock **198** sends the current time to the CPU **200**, which then compares the current time to the time of the event. Similarly, when the session device is the mobile device **250**, the clock **260** sends the current time to the processor **262**, which then compares the current time to the time of the event. When the current time has past the

15 time of the event start, the process continues to Step **456**. When the current time has not past the time of the event start, in Step **454**, the session device determines whether the time of the event is within a specified range of the current time (note, one skilled in the art will recognize that it is common practice in software programming to check to see if a timer value is within a specified range for example the application would

20 look for a range from 5 to 0 minutes before the event.) For example, when the session device is the fixed network device **196**, the timing clock **198** sends the current time to the CPU **200**, which then compares the current time to the specified range of the time of the event. Similarly, when the session device is the mobile device **250**, the clock

260 sends the current time to the processor **262**, which then compares the current time to the specified range of the time of the event. When the time of the event is not within a specified range of time, the process cycles back to node C and Step **442**.

When the time of the event is within a specified range of time, the process continues

5 at Step **456**.

In Step **456**, it is determined whether user presence is required. It will be appreciated that the method used in Step **456** can be substantially similar to the method used in Step **446** and herein described. When user presence is required in Step **456**, the process determines whether the online account user **64** is present at node
10 D and Step **458**. It will be appreciated by one of ordinary skill in the art that the method used in Step **458** can be substantially similar to the method used in Step **448** and herein described. When user presence is not detected in Step **458**, the process cycles back through node F to node C and Step **442**.

FIG. **21** is a flowchart illustrating more detail of the operation of the online
15 communication system **10** at Steps **448** and **458** of FIG. **20** in accordance with the preferred embodiment of the present invention. Beginning at node D and Step **472**, an initialization process is accomplished including activation of a motion sensor, setting of a timer threshold, and setting of a tilt sensor threshold. Next, in Step **474**, it is determined whether the motion sensor output is greater than the tilt sensor
20 threshold. In Step **476**, when the motion sensor output is greater than the tilt sensor threshold, the online account user **64** is considered to be present and the process continues to node E. In Step **478**, when the motion sensor output is not greater than the tilt sensor threshold, the timer output is compared to the timer threshold. When

the timer is not greater than the timer threshold, the process returns to Step 474. In Step 480, when the timer is greater than the timer threshold in Step 478, the online account user 64 is not present and the process continues to node F. Upon completion of Step 480, the process can cycle back to Step 474 to continue periodically checking for the presence of the online account user 64.

Referring back to FIG. 20, when user presence is not required in Step 456, or user presence is required in Step 456 and user presence is detected in Step 458, the process continues to Step 460. In Step 460, the session client 22 utilizes the plurality of session information 182 and the session server identification 180 previously stored in the application folder area to retrieve the latest information on the event from the online session site and begins to process the information. It will be appreciated by one of ordinary skill in the art that, at Step 460, the session client 22 can retrieve the latest information on the event or based upon an event stimulus. Next, in Step 462, the current state of the event retrieved from the event site is stored in the memory of the session device. For example, the current state of the event can be stored in the memory slot 286 for the online session 80 of the client data memory 284 of the session device. Next, in Step 464, the process determines whether the online session 80 has ended. In Step 466, when the online session 80 has ended, the session client 22 stores the results and other state information in the memory of the session device and alerts the online account user 64 of the session results. For example, the results and state information can be stored in the memory slot 286 for the online session 80 of the client data memory 284 of the session device. Types of state information that can be stored include the URL where results reside and the last URL visited. For an

auction online session, the state information can include the auction item description / identification, the sale amount, similar items, and the sellers store front URL. For a gambling online session, the state information can include the type of event (e.g.: football, racing or boxing) the score, prior history of related events for example who won the event the last time the same players met, and event odds. When the session has not ended in Step 464, the process continues to Step 468, wherein the online account user 64 is notified of the current state. Next, in Step 470, the online account user 64 is alerted preferably when the event is actionable. The process then cycles back to node C and Step 442.

Although the invention has been described in terms of preferred embodiments, it will be obvious to those skilled in the art that various alterations and modifications can be made without departing from the invention. Accordingly, it is intended that all such alterations and modifications be considered as within the spirit and scope of the invention as defined by the appended claims.

What is claimed is: